



WALL TO WALL

MUCHO MAS QUE ALFOMBRAS

ALADDIN[®]
by MOHAWK

CHARGED TILE




872 Fire Wall



658 Enviro



989 Fusion



595 Water Power



889 Eco Chic



919 Circuit



841 Heat Cell



579 Sustainable



879 Earth Source

Style Name	Charged Tile
Product Type	Modular
Construction	Tufted
Surface Appearance	Enhanced Loop graphics
Nylon Type	Colorstrand Nylon with MPP
Gauge	1/10 (39.37 rows per 10 cm)
Pile Weight	20.0 oz. per sq. yd. (678 g/m ²)
Pile Thickness	.147" (3.73 mm)
Stitches per inch	11.0 (43.31 per 10 cm)
Dye Method	Solution Dyed/Space Dyed
Protective Treatment	Sentry Plus
Density	4.898
Weight Density	97.960
Primary Backing	Reinforced Synthetic
Backing Foundation	Encycle Modular
Secondary Backing	Fiberglass Reinforced Thermoplastic Composite
Pattern Repeat	Not Applicable
Size	24" x 24" (.6096 m x .6096 m)
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Les than 450
Static Propensity	AATCC - 134 Under 3.5 KV
IAQ Green Label	39901930
IAQ Green Label Plus	3990
CRI Rating	Severe Traffic
Warranties	Lifetime Encycle Modular Warranty