



WALL TO WALL

MUCHO MAS QUE ALFOMBRAS

ALADDIN
by MOHAWK

DOWNLOAD TILE



936 Network



589 Memory



979 Hardware




877 Online



638 Document



558 Modem



889 Toolbar

| <u>STYLE NAME</u> | <u>DOWN LOAD TILE</u> |
|------------------------------|---|
| PRODUCT TYPE | Modular |
| CONSTRUCTION | Tufted |
| SURFACE APPEARANCE | Level Patterned Loop |
| NYLON TYPE | Colorstrand SD Nylon |
| GAUGE | 1/10 (39.37 rows per 10 cm) |
| PILE THICKNESS | .107" (2.72 mm) |
| STITCHES PER INCH | 8.0 (31.50 per 10 cm) |
| DYE METHOD | Solution Dyed |
| PROTECTIVE TREATMENT | Sentry Plus |
| DENSITY | 4.710 |
| WEIGHT DENSITY | 65.940 |
| PRIMARY BACKING | Reinforced Synthetic |
| SECONDARY BACKING | Fiberglass Reinforced Thermoplastic Composite |
| PATTERN REPEAT | Not Applicable |
| SIZE | 24" x 24" (.6096 m x .6096 m) |
| FLAMMABILITY - RADIANT PANEL | ASTM E 648 Class 1 (Glue Down) |
| SMOKE DENSITY | ASTM E 662 Less than 450 (Flaming Mode) |
| STATIC PROPENSITY | AATCC - 134 Under 3.5 KV |
| IAQ GREEN LABEL PLUS | 3990 |
| PERFORMANCE | Severe Traffic |
| WARRANTIES | Lifetime Encycle Modular Warranty Lifetime Limited Colorfastness to light 10 Year Limited Colorfastness to Atmospheric Contaminants |

Wall to Wall Alfombras

Libertad 1240 Local 13 - Capital Federal

Tel: 4815 - 7509 / 4813-8636

info@alfombraswall.com.ar - www.alfombraswall.com.ar