




First Meeting Modular EcoFlex



84050 Sandstone
17-1118 TPX



26021 Black Caviar
19-4007 TPX




86149 Bronze Statue
19-1015 TPX



86115 Burled Wood
16-1010 TPX



16124 City Street
18-0601 TPX



66027 Georgian Bay
17-6212 TPX



66119 Gothic Olive
19-0515 TPX



56152 Patrician Teak
18-1016 TPX




76151 Pewter Green
17-0517 TPX



16012 Skyscraper
18-5203 TPX



76156 Subway Rain
16-1107 TPX



56024 Upward Taupe
17-1310 TPX



55002 Waterway
18-4011 TPX

PRODUCT SPECIFICATIONS

Style Name..... First Meeting Modular EcoFlex
 Product Type..... Modular
 Construction Tufted
 Surface Appearance..... Level Solid Cut and Loop
 Nylon Type..... Colorstrand® SD Nylon
 Gauge 1/10 (39.37 rows per 10 cm)
 Pile Weight..... 26.0 oz. per sq. yd. (882 g/m²)
 Pile Thickness..... .108" (2.74 mm)
 Stitches Per Inch 11.0 (43.31 per 10 cm)
 Dye Method..... Solution Dyed
 Protective Treatment..... Sentry Plus
 Density 8,667
 Weight Density..... 225,342
 Primary Backing..... Non Woven Synthetic
 Backing Foundation Not Applicable

Secondary Backing EcoFlex Modular System
 Pattern Repeat..... Not Applicable
 Size..... 24" x 24" (.6096 m x .6096 m)
 Flammability ASTM E 648 Class 1 (Glue Down)
 Smoke Density ASTM E 662 Less than 450
 Static Propensity..... AATCC-134 Under 3.5 KV
 IAQ Green Label 4462271
 IAQ Green Label Plus..... 2771
 CRI Rating Heavy Traffic
 Warranties: Lifetime Limited Modular Warranty, Lifetime Limited
 Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric
 Contaminants, 10 Year Stain Warranty, Lifetime Static