



Logical Modular



1288 Exotic
18-5203 TPX, 19-0515 TPX



1291 Organic
16-1010 TPX, 18-1016 TPX



1378 Brilliant
18-5203 TPX, 19-0515 TPX



1457 Fresh
17-6212 TPX, 19-1015 TPX



6119 Wicked
17-0517 TPX, 19-0515 TPX



7020 Sparkling
16-1010 TPX, 16-1133 TPX



7025 Mega
18-0403 TPX, 19-4007 TPX



7081 Lucky
17-1019 TPX, 18-0403 TPX



7087 Psuedo
15-1225 TPX, 17-1019 TPX



7093 Rich
18-0403 TPX, 19-4025 TPX



7099 Hot
18-1016 TPX, 19-1420 TPX



7109 Delicious
18-1016 TPX, 19-1015 TPX



7111 Accidental
18-1016 TPX, 19-1015 TPX

PRODUCT SPECIFICATIONS

Style Name..... Logical Modular
 Product Type..... Modular
 Construction Tufted
 Surface Appearance..... Textured Patterned Cut and Loop
 Nylon Type..... Colorstrand® SD Nylon
 Gauge..... 1/12 (47.00 rows per 10 cm)
 Pile Weight..... 32.0 oz. per sq. yd. (1085 g/m²)
 Pile Thickness..... .155" (3.94 mm)
 Stitches Per Inch..... 11.5 (45.28 per 10 cm)
 Dye Method..... Solution Dyed
 Protective Treatment..... Sentry Plus
 Density..... 7,422
 Weight Density..... 237,824
 Backing Foundation..... Encycle® Modular by Durkan
 Primary Backing..... Reinforced Synthetic

Bonding Agent..... 100% PVC-Free Thermoplastic
 Secondary Backing..... Fiberglass Reinforced Thermoplastic Composite
 Pattern Repeat..... Not Applicable
 Size..... 24" x 24" (.6096 m x .6096 m)
 Recycled Content..... Minimum 35% pre-consumer by total weight
 Flammability..... ASTM E 648 Class 1 (Glue Down)
 Smoke Density..... ASTM E 662 Less than 450
 Static Propensity..... AATCC-134 Under 3.5 KV
 IAQ Green Label..... 39901930
 IAQ Green Label Plus..... 3990
 CRI Rating..... Severe Traffic
 Warranties: Lifetime Encycle Modular Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, Lifetime Static